



KGC-301/C



CC-Link IE TSN

CC-Link IE TSN Certified 10/100/1000Base-T to 100/1000Base-X Media Converters

Product Highlights:

- CC-Link IE TSN certified
- Industrial rated
- Full wire speed performance
- SFP flexibility
- Manual port configuration
- Link fault pass through function
- Low power consumption
- Options for Bi-Di communication
- Options for CWDM

The media converter is designed to convert three different line rates of copper Ethernet signals to/from two line rates of fiber signals. It is used to extend the connection distance up to 70km or more between two Gigabit Ethernet devices via fiber cable transparently with no performance degradation. With the SFP connector design, the media converter not only supports existing variety of multimode and single mode fibers, but also preserves the flexibility to adapt to any change of your fiber network in the future. The converter also can support Bi-Di WDM and CWDM fiber network applications

Key Features:

- CC-Link IE TSN certified and industrial rated
- Tri-speed 10/100/1000Mbps copper to dual-speed 1G/100Mbps fiber conversion
- Support full wire speed conversion
- Support jumbo frame conversion
- Provide direct conversion with shortest latency between two links in same line rates
- Support transparent conversion of any packet types with no packet modification
- Support auto-negotiation with link partners
- Provide link fault pass through function for media converter applications
- Provide SFP slot on fiber port for mounting variety of fiber options

Specifications:

Standard	IEEE 802.3i, 802.3u, 802.3z, 802.3ab, 802.3az	
Copper Port	Shielded RJ-45, 10/100/1000Mbps, Full/Half duplex Auto-negotiation, Auto-MDI/MDI-X	
Fiber Port	SFP connector with pre-configured SFP fiber transceiver 1G/100Mbps, Full duplex, Auto-negotiation FEFI (100FX), Remote fault signaling (1000FX)	
Network Cables	Copper port: Cat.5e recommended or higher up to 100m Fiber port: MMF 50/125µm, 62.5/125µm, SMF 9/125µm	
Port-to-Port Latency	1µs (Cut-through latency at all frame size conversion)	
LED Indication	Power status, port link status, port speed status	
Mounting	Desktop, Wall, DIN-Rail	
DC Power Input	Screwed terminal block: +/- contacts DC jack: -D 6.3mm/ +D 2.0mm Operating voltage range: +12V ~ +60VDC Consumption 2.4W max. @60V	
Environment	Operating Temperature:	-40°C ~ 75°C
	Storage Temperature:	-40°C ~ 85°C
	Relative Humidity:	5% ~ 90% non-condensing



Ordering Information:

KGC-301/C-X

Model Ext.	1000M Fiber			Distance
-	No SFP Transceiver			
-SX	LC	850	50/125 62.5/125	500m 200m
-LX	LC	1310	MMF SMF	550m 10km
-LX20	LC	1310	SMF	20km
-LX30	LC	1310	SMF	30km
-LX50	LC	1550	SMF	50km
-LX70	LC	1550	SMF	70km
-W3510	LC	Tx1310 Rx1550	Bi-Di SMF	10km
-W5310	LC	Tx1550 Rx1310	Bi-Di SMF	10km
-W3520	LC	Tx1310 Rx1550	Bi-Di SMF	20km
-W5320	LC	Tx1550 Rx1310	Bi-Di SMF	20km
-W3410	LC	Tx1310 Rx1490	Bi-Di SMF	10km
-W4310	LC	Tx1490 Rx1310	Bi-Di SMF	10km

Model Ext.	100M Fiber			Distance
-FM	LC	1310	MMF	2km
-FS30	LC	1310	SMF	30km
-FS60	LC	1310	SMF	60km
-FS100	LC	1550	SMF	100km
-FW3520	LC	Tx1310 Rx1550	Bi-Di SMF	20km
-FW5320	LC	Tx1550 Rx1310	Bi-Di SMF	20km



CC-Link I E TSN

Katron Technologies Inc.
 15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,
 Hsi-chih District, New Taipei City, Taiwan
 Tel: 886-2-2698-3878
 Fax: 886-2-2698-3873
 E-mail: kti@ktinet.com.tw
 URL: http://www.ktinet.com.tw

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.
 This information is subject to change without prior notice.

Dimension 72.5 x 108 x 23 mm (WxDxH)

Approval FCC Class A, CE mark Class A, VCCI Class A, CC-Link IE TSN

Fiber Optical Specifications:

Model Ext.	1000M Fiber	Wavelength	Tx Power*	Rx Sens.	Rx Max.
-SX	LC MMF	850nm	-9.5 ~ -4dBm	-18dBm	0Bm
-LX	LC SMF	1310nm	-9.5 ~ -3dBm	-20dBm	-3dBm
-LX20	LC SMF	1310nm	-8 ~ -2dBm	-23dBm	-1dBm
-LX30	LC SMF	1310nm	-4 ~ +1dBm	-24dBm	-3dBm
-LX50	LC SMF	1550nm	-4 ~ +1dBm	-24dBm	-3dBm
-LX70	LC SMF	1550nm	0 ~ +5dBm	-24dBm	-3dBm
-W3510	Bi-Di LC SMF	Tx 1310nm Rx 1550nm	-9 ~ -3dBm	-21dBm	-1dBm
-W5310	Bi-Di LC SMF	Tx 1550nm Rx 1310nm	-9 ~ -3dBm	-21dBm	-1dBm
-W3520	Bi-Di LC SMF	Tx 1310nm Rx 1550nm	-8 ~ -2dBm	-23dBm	-1dBm
-W5320	Bi-Di LC SMF	Tx 1550nm Rx 1310nm	-8 ~ -2dBm	-23dBm	-1dBm
-W3410	Bi-Di LC SMF	Tx 1310nm Rx 1490nm	-9 ~ -3dBm	-21dBm	-1dBm
-W4310	Bi-Di LC SMF	Tx 1490nm Rx 1310nm	-9 ~ -3dBm	-21dBm	-1dBm

Model Ext.	100M Fiber	Wavelength	Tx Power*	Rx Sens.	Rx Max.
-FM	LC MMF	1310nm	-20 ~ -14dBm	-31dBm	-8dBm
-FS30	LC SMF	1310nm	-15 ~ -8dBm	-34dBm	0dBm
-FS60	LC SMF	1310nm	-5 ~ 0dBm	-35dBm	0dBm
-FS100	LC SMF	1550nm	-5 ~ 0dBm	-35dBm	0dBm
-FW3520	Bi-Di LC SMF	TX 1310nm RX 1550nm	-14 ~ -8dBm	-32dBm	0dBm
-FW5320	Bi-Di LC SMF	TX 1550nm RX 1310nm	-14 ~ -8dBm	-32dBm	0dBm

*Data for 62.5/125µm MMF, 9 /125µm SMF