



# KGC-261-DP-AT/I Series



**IEC 61850-3  
Enhanced!**



## IEC 61850-3 IEEE 1613 Managed Media Converters with PoE+ PSE support

### Product Highlights:

- IEC 61850-3 & IEEE 1613 rated
- Tri-speed copper to dual-speed fiber conversion
- Advanced LFPT, OPA, ALS features
- PoE PSE functionality
- Variety of PoE options
- Web & SNMP management

### DC Input:



### Approval:

- FCC Class A, VCCI Class A
- CE mark Class A
- LVD IEC60950-1 safety
- EN 55032 emission
- EN 55024 immunity
- IEC 61850-3 EMC & environment
- IEC 60068-2-64 vibration
- IEC 60068-2-27 shock 30G test
- IEEE 1613 for power substation

### Key Features:

- IEC 61850-3 and IEEE 1613 industrial rated for power substation
- Tri-speed 10/100M/1Gbps copper to dual-speed 100M/1Gbps fiber conversion
- Comply with IEEE 802.3, 802.3u, 802.3ab, 802.3z, 802.3af, 802.3at standard
- Support full wire speed conversion for Gigabit copper to Gigabit fiber
- Provide dual-speed SFP on fiber port for mounting variety of fiber options
- Provide important LFPT (Link Fault Pass Through) media converter function
- Support Jumbo frame conversion
- Energy Efficient Ethernet (EEE) support
- Alarm events relay output
- Optical Power Alarm (OPA) function
- Auto Laser Shutdown (ALS) function
- Fiber support for multimode, short reach up to long reach single mode fiber, Bi-Di applications
- Web-based configuration management support
- Support SNMP management
- Provide variety of PoE options for different power level applications
- PoE shutdown protection for non-compliant PD, disconnection, over-current and short-circuit


### Specifications:

Standard	IEEE 802.3u, 802.3ab, 802.3z, 802.1ad, 802.3az, 802.1Q, 802.3af, 802.3at
Copper Port	Shielded RJ-45, 10/100/1000Mbps, Full/Half duplex, Auto-negotiation, Auto-MDI/MDI-X
Fiber Port	SFP connector with pre-configured SFP fiber transceiver 100Mbps/1Gbps Full duplex, Auto-negotiation, Far End Fault support
Network Cables	Copper port: Cat.5e recommended or higher up to 100m Fiber port: MMF 50/125µm, 62.5/125µm, SMF 9/125µm
Power over Ethernet	IEEE 802.3at compliant (High power PoE) 32W max. at port output for Cat.5 distance of 100 meters
LED Indication	Unit: power status, PoE status Per port: 1G/Link/Activity, 10-100/Link/Activity
Jumbo Frame size	Up to 9.6K bytes
DC TB Input	Flange terminal block: DC+/ DC-/ 3 Relay contacts Rated voltage range: +12 ~ +57VDC
Relay Output	3 dry contacts for NC & NO pairs on DC TB Contact rating: 30VDC/1A or 120VAC/0.5A Alarm events: power failure, configured port link fault, OPA




### EMI EMS Safety Environmental Tests:

Test	Standard	Specifications
FCC/EMI	FCC Rule Part 15	Class A
CE/EMC/EMI	EN 55032	Class A
CE/EMC/EMS	EN 55024	
ESD Test	IEC 61000-4-2	Contact: +/-8kV Air: +/-15kV
RS Test	IEC 61000-4-3	Strength: 20V/m
EFT/BURST	IEC 61000-4-4	DC IN: +/-4kV RJ-45: +/-4kV
Surge Immunity	IEC 61000-4-5	DC IN: +/-1kV RJ-45: +/-4kV
CS Test	IEC 61000-4-6	Level 3
Magnetic Field Imm.	IEC 61000-4-8	50/60Hz, 100A/m, 60s 50/60Hz, 1000A/m, 1s
Main Frequency Volt.	IEC 61000-4-16	Power: 300V Signal: 300V
Ripple on DC power	IEC 61000-4-17	10%
DOW Test	IEC 61000-4-18	Power: +/-2.5 Signal: +/-2.5
DC Dips	IEC 61000-4-29	Dips: 60% & 30%, 0.1s Interruption: 100%, 0.05s
Safety	EN 60950-1	
Dielectric Voltage	IEEE 802.3	TP, 1500VAC/60sec.
Insulation Resistance	IEEE 802.3	TP, 500VDC/10Mohm
Cold Test	IEC 60068-2-1 Ad	-40°C, 72hrs
Dry Heat Test	IEC 60068-2-2 Bd	+75°C, 30%RH, 72hrs
Damp Heat Test	IEC 60068-2-3 Ca	+75°C, 95%RH, 72hrs
Storage Test	IEC 60068-2-48	-40°C, 96hrs +85°C, 30%RH, 96hrs
Vibration Test	IEC 60068-2-64 Fh	10-150Hz, 2.0 g/Hz
Shock Test	IEC 60068-2-27 Ea	30G



DIN-Rail Dimension



Panel Dimension



**Katron Technologies Inc.**  
15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,  
Hsi-chih District, New Taipei City, Taiwan  
Tel: 886-2-2698-3878  
Fax: 886-2-2698-3873  
E-mail: kti@ktinet.com.tw  
URL: http://www.ktinet.com.tw

Trademarks: All brand names are trademarks or registered trademarks of their respective holders. This information is subject to change without prior notice.

DC Jack Input	Power jack (Contacts: -D6.3mm, +D2.0mm) Rated voltage range: +12 ~ +48VDC
DC DIN Input	Power DIN, Mini-DIN-4 socket Contact rating: 2.7A 48V Rated voltage range: +12 ~ +48VDC
DC Power	General: +12 ~ +57VDC PoE: +45 ~ +57VDC Polarity reversal protection
Power Consumption	5W max.@55V (Full load without PoE output) 37W max.@55V (Full load with PoE+ max. output)
Housing	Enclosed metal with no fan
Environment	Operating Temperature: -40°C ~ 75°C Storage Temperature: -40°C ~ 85°C Relative Humidity: 5% ~ 95% non-condensing
Dimension	40 x 106 x 140 mm (WxDxH)
Mounting Support	DIN-Rail, Panel (optional)
MTBF	250K hours min

### Management:

Management	Web-based browser interface, SNMP manager Port Control Operating mode, Flow control, LLDP, PoE control
Packet Filtering	802.1Q tagged packet filtering, Untagged packet filtering
802.1Q VLAN	Ingress 802.1Q tag stripping, Egress 802.1Q tagging (tag insertion) S-tag tagging (802.1ad double tagging)
Maintenance	Restore factory default, reboot, firmware update
SNMP	Trap events: Bootup, Login failure, Port link changes, OPA SNMP Private MIB: DDM, Remote boot, OPA, PoE

### Fiber Optical Specifications:

1Gbps	Fiber Port	Wavelength	Tx Power*	Rx Sens.	Rx Max.	Distance*
-SX	LC 62.5/125 MMF 50/125 MMF	850nm	-9.5 ~ -4dBm	-18dBm	0Bm	220m 500m
-LX	LC MMF SMF	1310nm	-9.5 ~ -3dBm	-20dBm	-3dBm	550m 10km
-LX70	LC SMF	1550nm	0 ~ +5dBm	-24dBm	-3dBm	70km
-W3510	Bi-Di LC SMF	Tx 1310nm Rx 1550nm	-9 ~ -3dBm	-21dBm	-1dBm	10km
-W5310	Bi-Di LC SMF	Tx 1550nm Rx 1310nm	-9 ~ -3dBm	-21dBm	-1dBm	10km
100Mbps Fiber Port	Wavelength	Tx Power*	Rx Sens.	Rx Max.	Distance*	
-FM	LC MMF	1310nm	-20 ~ -14dBm	-31dBm	0dBm	2km
-FS30	LC SMF	1310nm	-15 ~ -8dBm	-34dBm	0dBm	30km

\* Tx Power data for 62.5/125µm MMF, 9/125µm SMF  
Distance: reference connection distance